



## 85V N-Channel Enhancement Mode Power MOSFET

**Description**

WMM053NV8HGS uses Wayon's advanced power trench MOSFET technology that has been especially tailored to minimize the on-state resistance and yet maintain superior switching performance. This device is well suited for high efficiency fast switching applications.

**Features**

- $V_{DS} = 85V$ ,  $I_D = 125A$
- $R_{DS(on)} < 5.5m\Omega$  @  $V_{GS} = 10V$
- High Speed Power Switching
- Low Gate Charge
- Low  $R_{DS(ON)}$
- 100% EAS Guaranteed

**Applications**

- Battery Management System
- Power Management Switching
- Motor Drive

**Absolute Maximum Ratings ( $T_c = 25^\circ C$ , unless otherwise noted)**

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	85	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current  $T_c = 25^\circ C$	$I_D$	125	A
		79	
Pulsed Drain Current <sup>4</sup>	$I_{DM}$	500	A
Single Pulse Avalanche Energy <sup>3</sup>	<b>EAS</b>	204.8	mJ
Total Power Dissipation <sup>4</sup>	$P_D$	162	W
Operating Junction and Storage Temperature Range	$T_J$ , $T_{STG}$	-55 to 150	°C

**Thermal Characteristics**

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction-to-Ambient <sup>1</sup>	$R_{JA}$	58	°C/W
Thermal Resistance from Junction-to-Lead	$R_{JC}$	0.77	°C/W

**Electrical Characteristics (T<sub>c</sub> = 25°C, unless otherwise noted)**

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	85	-	-	V
Gate-body Leakage current	I <sub>GSS</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±20V	-	-	±100	nA
Zero Gate Voltage Drain Current T <sub>J</sub> =25°C	I <sub>DS</sub>	V <sub>DS</sub> = 80V, V <sub>GS</sub> = 0V	-	-	1	μA
T <sub>J</sub> =100°C			-	-	100	
Gate-Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	2	3	4	V
Drain-Source on-Resistance <sup>2</sup>	R <sub>DSD(on)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 20A	-	4.6	5.5	mΩ
Forward Transconductance <sup>2</sup>	g <sub>fs</sub>	V <sub>DS</sub> = 5V, I <sub>D</sub> = 20A	-	55	-	S
<b>Dynamic Characteristics</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 40V, V <sub>GS</sub> = 0V, f = 1MHz	-	4645	-	pF
Output Capacitance	C <sub>oss</sub>		-	673	-	
Reverse Transfer Capacitance	C <sub>rss</sub>		-	41	-	
<b>Switching Characteristics</b>						
Gate Resistance	R <sub>g</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = 0V, f = 1MHz	-	1.8	-	Ω
Total Gate Charge	Q <sub>g</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 40V, I <sub>D</sub> = 50A	-	61.3	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	21	-	
Gate-Drain Charge	Q <sub>gd</sub>		-	11	-	
Turn-on Delay Time	t <sub>d(on)</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 40V, R <sub>G</sub> = 3Ω, I <sub>D</sub> = 50A	-	16.5	-	ns
Rise Time	t <sub>r</sub>		-	51.8	-	
Turn-off Delay Time	t <sub>d(off)</sub>		-	37.1	-	
Fall Time	t <sub>f</sub>		-	8.2	-	
<b>Drain-Source Body Diode Characteristics</b>						
Diode Forward Voltage <sup>2</sup>	V <sub>SD</sub>	I <sub>S</sub> = 50A, V <sub>GS</sub> = 0V	-	-	1.2	V
Continuous Source Current <sup>1,5</sup>	I <sub>S</sub>	V <sub>G</sub> = V <sub>D</sub> = 0V, Force Current	-	-	125	A
Reverse Recovery Time <sup>2</sup>	t <sub>rr</sub>	I <sub>F</sub> = 20A, di/dt = 100A/μS	-	69	-	ns
Reverse Recovery Charge <sup>2</sup>	Q <sub>rr</sub>		-	141	-	nC

**Notes:**

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
3. The EAS data shows Max. rating . The test condition is V<sub>DD</sub>=35V, V<sub>GS</sub>=10V, L=0.4mH, I<sub>AS</sub>=32A
- 4.The power dissipation is limited by 150°C junction temperature
- 5.The data is theoretically the same as I<sub>D</sub> and I<sub>DM</sub> , in real applications , should be limited by total power dissipation.

## Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics







Figure 3. Forward Characteristics of Reverse

Figure 4.  $R_{DS(ON)}$  vs.  $V_{GS}$ Figure 5.  $R_{DS(ON)}$  vs.  $I_D$ Figure 6. Normalized  $R_{DS(on)}$  vs. Temperature




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Power Dissipation




Figure 10. Safe Operating Area









Figure 11. Normalized Maximum Transient Thermal Impedance

**Test Circuit****Figure A. Gate Charge Test Circuit & Waveforms****Figure B. Switching Test Circuit & Waveforms****Figure C. Unclamped Inductive Switching Circuit & Waveforms**

## Mechanical Dimensions for TO-263


## COMMON DIMENSIONS



SYMBOL	MM	
	MIN	MAX
A	4.37	4.89
A1	1.17	1.42
A2	2.20	2.90
A3	0.00	0.25
b	0.70	0.96
b1	1.17	1.47
c	0.28	0.60
D1	8.45	9.30
D4	6.60	-
E	9.80	10.40
E5	7.06	-
e	2.54BSC	
H	14.70	15.70
H2	1.07	1.47
L	2.00	2.80
L1	-	1.75
L4	0.254BSC	
θ	0°	9°

**Ordering Information**

Part	Package	Marking	Packing method
WMM053NV8HGS	TO-263	WMM053NV8HGS	Tape and Reel

**Marking Information**

WMM053NV8HGS = Device code

WWXX XXX= Date code

**Contact Information**

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

WAYON® is registered trademarks of Wayon Corporation.

**Disclaimer**

WAYON reserves the right to make changes without further notice to any Products herein to improve reliability, function, or design. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. WAYON does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Products or technical information described in this document.